

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number
WO 2005/046382 A1

(51) International Patent Classification⁷: **A45B 19/00**

(21) International Application Number: **PCT/CN2004/001275**

(22) International Filing Date: **9 November 2004 (09.11.2004)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data: **03108176.6 12 November 2003 (12.11.2003) CN**

(71) Applicant and
(72) Inventor: **HO, Wing Hang [CN/CN]; Flat G, 9th Floor, June Garden Tower 3, 28 Tung Chau Street, Kowloon, Hong Kong (CN).**


(74) Agent: **NTD PATENT & TRADEMARK AGENCY LIMITED BEIJING OFFICE; 10th Floor, Block A, Investment Plaza 27, Jinrongdajie, Beijing 100032 (CN).**

(81) Designated States (unless otherwise indicated, for every kind of national protection available): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): **ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,**

[Continued on next page]

(54) Title: UMBRELLA DEVICE



(57) Abstract: The present invention relates to an umbrella device that has a canopy, a canopy mechanism adapted to expand and collapse said canopy, a base, an arm assembly disposed between said base and said canopy mechanism, said arm assembly having a proximal end pivotally connected to said base and a distal end pivotally connected to said canopy mechanism, said arm assembly being operable, by pivoting said proximal end relative to said base, between a retracted configuration and a protracted configuration, said arm assembly protracting when said proximal end pivots in a first pivotal direction and retracting when said proximal end pivots in a second opposite pivotal direction. The canopy mechanism may be disposed in a first direction relative to said base in said retracted configuration and in a second direction relative to said base, substantially transverse to said first direction, in said protracted configuration.

WO 2005/046382 A1



FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.